



### PRODUCT CATALOGUE

Bringing Your Imagination Into a Reality

www.obbysventure.co.ke



### WHO WE ARE

Obby's Ventures is your one stop specialized events company with a holistic and professional understanding of the events industry in today's dynamic era. We take great satisfaction in understanding our client's vision and making it a reality.

We bring personalized event closer to you and help create relationships that last. Using digital modelling technology, we can assist our clients with visualizing their event so as to optimize every aspect.

No event is too large nor too small and each event gets our full attention. Our obsession on details and dedication to perfection, we can bring to life anything that you can imagine. Whether you are planning a private event, a cooperate award banquet, a trade show, A.G.Ms, a Conference, an exhibition or a Cocktail, Obby's Ventures will ensure that your event is tactfully designed by our competent technical engineers and graphic designers leaving you with fun and extraordinary results.

#### MAKE YOUR DAY MEMORABLE



## SOUND Section











Flying Bar AD-L6A

Supports 1 Ton, Hanging Belt, U-ring



Mixer

32ch digital

**Behringer wing** 

Stage Box Behringer S32

32-channel Digital Snake with Remote-controllable Midas-designed Mic Pres, an AES50 Network Port with Klark Teknik SuperMac Technology, and Ultranet Integration with Powerplay P16 Systems







#### ADMARK AD-L6A

2x2.5"Neo,4Ohm 160W,Celestion from UK ,neodynium

2000W active 3-way double 12" line-array MF: 4x6.5" Neo,80hm,600W LF: 2x12"Neo,1200W ,80hm, Celestion from UK, neodynium With 4 channel amplifier,Class-D, output power.500W+900W+2000W/80hm, with built-in DSP made in Germany



2X18" Subwoofer,3000W. With(2000W+2000W Amplifier) Class-D amplifier With DSP Components:2\*18"Low Frequency range:40Hz~130Hz (±3dB) Rated /Program power(RMS/peak):3000W/6000W Sencitivity(1 W/m):113dB Rated Maximum SP:143dB (peak@1m) Input Impedance:20 K $\Omega$ Input Sensitivity: 0.775V Output Power:2000W/8Ω+2000W/8Ω Distortion: < 0.05% Pow Connector: Power Con Operating Voltage: 120v 220V 50/60Hz Colour: Black/White Weight:48Kg Dimensions (W×D×H):582×730 ×1180mm



#### ADMARK AX18BA

1X18" Subwoofer,1200W. With(2700W Amplifier) Class-D amplifier With German DSP ()Components:1"18"Low (2)Frequency range:40Hz~130Hz (±3dB) (3)Rated /Program power(AES/ peak):1200W/2400W (4) Sencitivity(I W/m):106dB (5)Rated Maximum SP:136dB ( peak@1m) (6)Input Impedance:20 KΩ (2)Input Sensitivity:0.775V (8)Output Power:2700W/4Ω (9)Distortion:-0.05% (10)Pow Connector:Power Con (10)Operating Voltage:120v 220V 50/60Hz (2)Colour:Black/White (13)Weight:54Kg (4)Dimensions (W×D×H):640×780×560mm



ADMARK AT-15A

ADMARK

**AD728A** 

15"active monitor speaker: 10 HF: 1x1.75",16ohm 75W Celestion from UK 20 MF:1\*15",16ohm.400w 3 amp output-power:800@8ohr

SOUND SECTION

2 B E

# LIGIHTING







LED 18\*40W Laser Bee-eye

POWER SUPPLIES:100-240W

LED SOURCE:18X40W RGBW

temperature:2500 -<mark>8000</mark>K OPTICS:4°-60°Electronic Zoom angle

LED Strips: 5050RGB 83PCS 0.12W

Laser power: 8W RGB laser Color

Osram LEDs,50,000 h

50/60HZ



#### ANNUAL MEETINGU

#### Waterproof LED Par Light 18x10W RGBW4IN1

Voltage:AC100V-240V.50/60Hz Light Source:18\*10W RGBW4IN1 LEDs Power: 200W Beam angle:25" DMX channel:8CH Control mode:DMX 512,Auto Run,Sound Active,Master-slave IP rate: IP65

#### Waterproof 380W Beam

Input Voltage:100-240V 50/60 Hz Light Source:Osram 371W Gobos:one static gobo wheel: 16 gobos + open Color:one wheel color ,14 colors+ open, half-color and rainbow effect Prism:8 facet prism, Beam angle:1.2°



#### **LED Waterproof Strobe**

Input Voltage:100-240V 50/60 Hz Light Source:Osram 371W Gobos: one static gobo wheel: 16 gobos + open Color: one wheel color .14 colors+ open, half-color and rainbow effect Prism: 8 facet prism, Beam angle:1.2°

**BB** 

#### **LED Indoor Strobe**

Input voltage: 100-240V 50-60Hz LED Source: 800PCS\*0.2W RGB LED+144PCS 0.5W white LED LED lifetime: 100000 hours Light Emitting Devices: Ultra High Brightness LED Power consumption: 600W Control Channel: 4/6/9/12/32/44CH

#### **LED RGB Strobe**

Voltage: AC100-240V 50/60HZ Power: 300W LED source: 240pcs WW LED +480PCS 3 in 1 RGB LED Control mode: DMX512, auto run, master-slave, sound active, with RDM function. Channel: 3/8/48/53CH

LIGINTING SECTION







#### Waterproof LED RGBW Strobe PL-E025W

Voltage: AC100-240V 50/60HZ Power: 340W Control mode: DMX512, self- propelled, master-slave, voice control, with RDM function. Channel: CH04, CH16, CH85, CH161

Dimming: 32bit 0~100% linear dimming

#### 3000W Low Fog Machine PL-I023

Power: 3000W Control: Manual, DMX-512, remote control Warm-up Time: 5-8 minutes Fog liquid capacity: 2L



#### LED Smoke Machine PL-1022

Voltage:AC 220V-240V 50/60Hz Current limit of insurance:8A/250V Power:1500W LED power: 18\*3W RGB single color LED Oil drum volume:3L Adjust output wind:support DMX-512:8CH Control :LCDoontroller, Remote

22 224



#### Sparkcular Machine PL-K003

Voltage: AC220V 50-60Hz Power: 300W Spray height: 3-3.5m for large consumables Medium consumables 2-2.5m



#### 200W LED Prefocus Profile Light PL-P202B

LED POWER: 200W Color Rendering Index(CRI): Ra≥ 90,Max can be 97 Voltage: AC90- 260V Max.power consumption: 200W/250W/260W/390W Fixed Lens: 19°/26°/36°/50° (optional) LED Life Time: over 50,000 hours LED 12\*40W Moving Matrix with Zoom PL-L480M

Voltage: AC 100V~240V 50/60Hz Rated power :560W LED: 12 x 40W 4in1 RCBW LED Beam angle: 4-37° Average lifetime: ≥ 50000H Tilt: 240°( 8bit/16bit precision scanning) Colour: Homogeneous RCB Input Voltage: 100-240V 50/60 Hz



Waterproof 400W 3 in 1 Moving Head PL-W400BWS Light Source: Osram 371W, 7600K, 4000 hours Cobos: one Static gobo wheel: 14 gobos + open one Rotating gobo wheel: 7 interchangeable rotating gobos + open,

LIGINTING SECTION





### TENTS SECTION









#### Tent 20M X 60M X4M

Tent

20M X 80M X4M

Aluminum Structure Tent Size: 20m x40m

Aluminum Structure Tent Size: 20m x40m Edge Height: 4m top height:7.2m Bay distance: 5 meters, Total 5 bay. Structure: Hard pressed extruded Aluminum alloy T6061/T6 203\*112\*3mm Roof cover:850g/sqm PVC/ Side wall : 650g/sqm PVC Color: white and transparent windows (SGS DIN 4102-1 B1 class for Flamibility) windload: 120km/h Snowload: 75kg/sqm temperature: -30 to +60degree with full accessories, steel bases, expansion screws Life: 10years for the cover, 20 years for aluminum alloy structure

Fixing method: the expansion screw is fixed to the cement floor. If It's grass, sand, or other ground, you'll need extra accessories.







Fixing method: the expansion screw is fixed to the cement floor. If It's grass, sand, or other ground, you'll need extra accessories.

#### Acrum tent 30M X 80M X4M

Roof cover:1100g/sqm PVC/ Side wall : 650g/sqm PVC color: transparent. For the 20x40x4m tent

#### **A Decorative Veil**

For 20x40x4m (Contains tops, triangles and walls) Colors are optional 2 fold



TENTS SECTION











#### Pagoda Tent 6m x 6m x 2.4m

Aluminum Frame+Cloth Aluminum Structure Tent Size: 6m\*6m\*2.4m top height:5.8m

Structure: Hard pressed extruded Aluminum alloy T6061/T6 65\*65\*2.5mm Roof cover:850g/sqm Side wall : 650g/sqm PVC Cloth color:white and transparent windows (SGS DIN 4102-1 B1 class for Flamibility) transparent window on 4 sides wall.

windload: 120km/h Snowload: 85kg/sqm

temperature: -30 to +60degree

with full accessories, steel bases, expansion screws Life: 10years for the cover, 20 years for aluminum alloy structure

Fixing method: the expansion screw is fixed to the cement floor. If It's grass, sand, or other ground, you'll need extra accessories.

#### **A Decorative Veil**

For 6x6x2.4m(Contains tops, triangles and walls) Colors are optional Top is 3 fold,wall is 2 fold.

#### Pagoda Tent 10m x 10m x 2.6m

Aluminum Frame+Cloth Aluminum Structure Tent Size: 10m\*10m\*2.6m top height:6.8m

Structure: Hard pressed extruded Aluminum alloy T6061/T6 122\*68\*3mm Roof cover:850g/sqm Side wall : 650g/sqm PVC Cloth color:white and transparent windows (SCS DIN 4102-1 B1 class for Flamibility) transparent window on 4 sides wall.

windload: 120km/h Snowload: 85kg/sqm

temperature: -30 to +60degree

with full accessories, steel bases, expansion screws Life: 10years for the cover, 20 years for aluminum alloy structure

Fixing method: the expansion screw is fixed to the cement floor. If It's grass, sand, or other ground, you'll need extra accessories.

#### **A Decorative Veil**

For 10x10x2.6m(Contains tops, triangles and walls Colors are optional Top is 3 fold,wall is 2 fold.



TENTS SECTION



# **Decor, Tents, Chairs**



### FLOORING, CARPETTING AND EXHIBITION BOOTHS





# **TRUSSING AND STAGE**





# **EXECUTIVE TOILETS**









we provide professional event live streaming & broadcasting services in Kenya for small & large events. We also provide professional video cameras and live streaming equipment with lighting gears, lapels and lavaliers for interviews & capturing sound separately.





We stream on different platforms, Multi- social platforms Live Streaming and Web-casting Services of Events

we also provide:
Creative production
On-camera Obbys creative team
Post-production highlights & reels

Obbys is ready for your next event (Video & Photography) and activities like: • Concerts

- Corporate events & conferences
- Live Church Services
- Live Press Conferences for your project
- Product Launches
- Awards show red carpet coverage
- Branded content
- Hybrid Events

Contact Us Today  $\rightarrow$ 

### WHENEVER

your decisions require wide industry experience, quality and reliability of Audio-Visual technology solutions, timeliness of deliverables, then OBBY'S VENTURES is your 'to go to' partner.











-11111-6-1-1

0 0

www.obbysventure.co.ke